
	Material Safety Data Sheet		24 Hour Emergency Phone Numbers: Medical/Poison Control: In U.S.: Call 1-800-222-1222 Outside U.S.: Call your local poison control center Transportation/National Response Center: 1-800-535-5053 1-352-323-3500
			<p>.....</p> <p>•NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.</p> <p>.....</p>

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this MSDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

Section 1 - Chemical Product / Company Information

This Material Safety Data Sheet is available in American Spanish upon request.
Los Datos de Seguridad del Producto pueden obtenerse en Español si lo requiere.

Product Name:	Phenopatch Elastomeric Smooth Patch Gun Grade	Revision Date:	05/30/2012
Product UPC Number:	070798122741	Supersedes:	08/14/2007
Product Use/Class:	Ready To Use Spackle/Wallboard Repair	MSDS Number:	00079949005
Manufacturer:	PHENOMENAL BRANDS PhenoPatch Products A Division of DAP Products Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 410-779-3265 (non-emergency matters)		

Section 2 - Hazards Identification

Emergency Overview: A(n) white to off-white paste product with a slight odor. **WARNING!** May cause eye, skin, nose, throat and respiratory tract irritation. Removal of this product after use or by dry sanding will generate dust and exposure to this dust may be irritating to the eyes, ears, nose and mouth. Harmful by inhalation and if swallowed. If dry-sanded, exposure to dust may result in build-up of material in eyes, ears, nose, and mouth.

Refer to other MSDS sections for other detailed information.

Effects Of Overexposure - Eye Contact: May cause eye irritation.

Effects Of Overexposure - Skin Contact: May cause skin irritation. May cause dry skin.

Effects Of Overexposure - Inhalation: Inhalation of high vapor concentrations can cause central nervous system depression and narcosis. Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation of dust may cause lung damage or other adverse pulmonary and respiratory effects.

Effects Of Overexposure - Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion may result in obstruction when material hardens.

Effects Of Overexposure - Chronic Hazards:

The International Agency for Research on Cancer (IARC) has determined that crystalline silica in the form of quartz or

crystalite that is inhaled from occupational sources is carcinogenic to humans (Group 1- carcinogenic to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (published in June 1997) in conjunction with the use of these materials. The National Toxicology Program (NTP) classifies respirable crystalline silica as "known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (Group A2).

Breathing dust containing respirable crystalline silica may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may have the following serious chronic health effects: Excessive inhalation of respirable dust can cause pneumoconiosis, a respiratory disease, which can result in delayed, progressive, disabling and sometimes fatal lung injury. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. Smoking exacerbates this disease. Individuals with pneumoconiosis are predisposed to develop tuberculosis. There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by fibrosis of the lungs, skin and other internal organs) and kidney disease.

Primary Route(s) Of Entry: Skin Contact, Inhalation, Ingestion, Eye Contact

Medical Conditions which May be Aggravated by Exposure: If dry sanded, asthma and asthma-like conditions may worsen from prolonged or repeated exposure to dust.

Carcinogenicity:

CAS No.	Chemical Name	ACGIH	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	Not Listed.	Not Listed.	Possibly carcinogenic to humans.	Not Listed.
14808-60-7	Silica, crystalline	Suspected human carcinogen.	Not Listed.	Carcinogenic to humans.	Known To Be Human Carcinogen.

Section 3 - Composition / Information On Ingredients

Chemical Name	CASRN	Wt%
Limestone	1317-65-3	40-70
Stoddard solvent	8052-41-3	1-5
Titanium dioxide	13463-67-7	0.5-1.5
Silica, crystalline	14808-60-7	0.1-1.0

Section 4 - First Aid Measures

First Aid - Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

First Aid - Skin Contact: Wash off immediately with soap and plenty of water.

First Aid - Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

First Aid - Ingestion: Call a physician or Poison Control Center immediately. Do not induce vomiting. Harmful or fatal if liquid is aspirated into the lungs. If swallowed, drink 8-10 oz. of water, get immediate medical attention.

Note to Physician: None.

COMMENTS: If over-exposure occurs, call your poison control center at 1-800-222-1222.

Section 5 - Fire Fighting Measures

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam, Water Fog

Unusual Fire And Explosion Hazards: None known.

Special Firefighting Procedures: Cool fire-exposed containers using water spray.

Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Wear proper protective equipment as specified in Section 8. Scrape up dried material and place into containers.

Section 7 - Handling And Storage

Handling: KEEP OUT OF REACH OF CHILDREN! Avoid contact with skin and eyes. Do not breathe dust. Removal of this product after use will result in the generation of Dust. If dry-sanded, exposure to dust may result in the build-up of material in eyes, ears, nose, and mouth which may cause irritation. Avoid excessive heat and handling. Wash thoroughly after handling.

Storage: Avoid excessive heat and freezing. Keep tightly closed. Do not store at temperatures above 120 degrees F. Store away from caustics and oxidizers.

Section 8 - Exposure Controls / Personal Protection

Chemical Name	CASRN	ACGIH TWA	ACGIH STEL	ACGIH CEIL	OSHA TWA	OSHA STEL	OSHA CEIL	Skin
Limestone	1317-65-3	10 MGM3	N.E.	N.E.	5 MGM3 (respirable fraction)	N.E.	N.E.	No
Stoddard solvent	8052-41-3	100 PPM	N.E.	N.E.	500 PPM	N.E.	N.E.	No
Titanium dioxide	13463-67-7	10 MGM3	N.E.	N.E.	15 MGM3	N.E.	N.E.	No
Silica, crystalline	14808-60-7	0.025 MGM.	N.E.	N.E.	10/(%SiO ₂ + 2) MGM3	N.E.	N.E.	No

Exposure Notes:

14808-60-7 The 2002 ACGIH Threshold Limit Values for Chemical Substances and Physical Agents lists the median Respirable Particulate Mass (RPM) point for crystalline silica at 4.0 microns in terms of the particle's aerodynamic diameter.

The TLVs for crystalline silica represent the respirable fraction.

OSHA PEL TWA for Quartz is calculated using the following formula: $10 \text{ mg/m}^3 / (\% \text{ SiO}_2 + 2)$. Both concentration and percent quartz for the application of this limit are to be determined from the fraction passing a size selector with the following characteristics.

Aerodynamic diameter (unit density sphere)	Percent passing selector
2	90
2.5	75
3.5	50
5.0	25
10	0

Precautionary Measures: Contact lenses pose a special hazard; soft lenses may absorb and all lenses concentrate irritants.

Engineering Controls: Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits. Prevent build-up of dust and vapors by opening windows and doors or use other means to ensure fresh air entry during application, drying and sanding. Wet sanding is recommended to avoid generation of dust.

Respiratory Protection: If concentrations exceed the exposure limits specified, use of a NIOSH-approved supplied air respirator is recommended. Where the protection factor is exceeded, use of a Self Contained Breathing Apparatus (SCBA) may be necessary. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Use an approved NIOSH/OSHA respirator if dry sanded.

National Institute for Occupational Safety and Health (NIOSH) has recommended that the permissible exposure limit be changed to 50 micrograms respirable free silica per cubic meter of air (0.05 mg/m³) as determined by a full shift sample up to 10-hour work shift.

Skin Protection: Wear gloves with repeated or prolonged use.

Eye Protection: Safety glasses with side-shields.

Other protective equipment: Not required under normal use.

Hygienic Practices: Remove and wash contaminated clothing before re-use.

Important: Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); these limits may vary between states.

Note: An employee's skin exposure to substances having a "YES" in the "SKIN" column in the table above shall be prevented or reduced to the extent necessary under the circumstances through the use of gloves, coveralls, goggles or other appropriate personal protective equipment, engineering controls or work practices.

Section 9 - Physical And Chemical Properties

Boiling Range:	Not Established	Vapor Density:	Heavier Than Air
Odor:	Slight	Odor Threshold:	Not Established
Color:	White to Off-White	Evaporation Rate:	Slower Than n-Butyl Acetate
Solubility in H₂O:	Not Established	Specific Gravity:	1.66 - 1.66
Freeze Point:	Not Established	pH:	Between 7.0 and 12.0
Vapor Pressure:	Not Established	Viscosity:	Not Established
Physical State:	Paste	Flammability:	Non-Flammable
Flash Point, F:	Greater than 200	Method:	(Seta Closed Cup)
Lower Explosive Limit, %:	Not Determined	Upper Explosive Limit, %:	Not Determined

When reported, vapor pressure of this product has been calculated theoretically based on its constituent makeup and has not been determined experimentally.

(See section 16 for abbreviation legend)

Section 10 - Stability And Reactivity

Conditions To Avoid: Excessive heat and freezing.

Incompatibility: Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products: Normal decomposition products, i.e., CO_x, NO_x.

Hazardous Polymerization: Hazardous polymerization will not occur under normal conditions.

Stability: Stable under normal conditions.

Section 11 - Toxicological Information

Product LD50: Not Established

Product LC50: Not Established

None

Significant Data with Possible Relevance to Humans: None.

Section 12 - Ecological Information

Ecological Information: Ecological injuries are not known or expected under normal use.

Section 13 - Disposal Information

Disposal Information: Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

EPA Waste Code if Discarded (40 CFR Section 261): None.

Section 14 - Transportation Information

DOT Proper Shipping Name:	Not Regulated.	Packing Group:	N.A.
DOT Technical Name:	N.A.	Hazard Subclass:	N.A.
DOT Hazard Class:	N.A.	DOT UN/NA Number:	N.A.

Note: The shipping information provided is applicable for domestic ground transport only. Different categorization may apply if shipped via other modes of transportation and/or to non-domestic destinations.

Section 15 - Regulatory Information

CERCLA - SARA Hazard Category:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Immediate Health Hazard, Chronic Health Hazard

SARA Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

None

Toxic Substances Control Act:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product:

Chemical Name	CAS Number
Non-Hazardous Polymer	Proprietary
Water	7732-18-5

Pennsylvania Right-to-Know:

The following non-hazardous ingredients are present in the product at greater than 3%:

Chemical Name	CAS Number
Non-Hazardous Polymer	Proprietary
Water	7732-18-5

California Proposition 65:

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Section 16 - Other Information**HMIS Ratings:**

Health: 1 Flammability: 1 Reactivity: 0 Personal Protection: X

Volatile Organic Compounds (VOC), less water less exempts: g/L: 51.2 lb/gal: 0.43 wt:wt%: 2.3

Volatile Organic Compounds (VOC), less water less exempts, less LVP-VOCs: wt:wt%: 1.6

REASON FOR REVISION: Periodic Update

Legend:

N.A. – Not Applicable

ACGIH – American Conference of Governmental Industrial Hygienists

N.E. – Not Established

SARA – Superfund Amendments and Reauthorization Act of 1986

N.D. – Not Determined

NJRTK – New Jersey Right-to-Know Law

VOC – Volatile Organic Compound

OSHA – Occupational Safety and Health Administration

PEL – Permissible Exposure Limit

HMIS – Hazardous Materials Identification System

TLV – Threshold Limit Value

NTP – National Toxicology Program

CEIL – Ceiling Exposure Limit

STEL – Short Term Exposure Limit

LD50 – Lethal Dose 50

LC50 – Lethal Concentration 50

F – Degree Fahrenheit

MSDS – Material Safety Data Sheet

C – Degree Celsius

CASRN – The Chemical Abstracts Service Registry Number

PHENOMENAL BRANDS believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. **NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS.** Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.

<End of MSDS>