



# TECHNICAL DATA SHEET

1/25/2018

## DAP® PHENOPATCH® PRE-MIXED STUCCO REPAIR



**Product Description:** DAP® PHENOPATCH® Pre-Mixed Stucco Patch is an easy to use patching compound for repairing minor cracks in stucco surfaces. It creates a hard durable patch which, when painted, blends evenly with the original stucco. It is mildew and weather resistant and can be used for interior or exterior applications.

### Suggested Uses:

Ideal for repairing cracks, holes and breaks in interior and exterior stucco surfaces.



**Perfect for Repairing  
Cracks & Breaks**



**Weather Resistant**



**Dries Hard for  
a Durable Finish**

### Featured & Benefits:

- Repairs cracks & breaks in stucco surfaces
- Mildew & weather resistant
- Creates a hard, durable finish
- Ready-to-use
- Interior/Exterior use

### Available In:

SKU #	Description	Size	Package Type	Case Pack	Color
7079864811	DAP® Pre-Mixed Stucco Repair	32 Fl. Oz. (946 mL)	Tub	8 PK	TBD
7079860817	DAP® Pre-Mixed Stucco Repair	128 Fl. Oz (3.78 L)	Tub	2 PK	TBD



# TECHNICAL DATA SHEET

## Surface Preparation & Application Instructions:

### Preparation:

- Surface to be patched must be clean, dry and free of loose paint, plaster, wax, dust and dirt.
- Apply in temperatures 40°F and above. The surface temperature must be above 40°F for at least 24 hours.
- No mixing is required.

### Application:

- Apply stucco patch with a clean putty knife or trowel.
- Thin cracks may be repaired with one application. For fills over 1/4" deep, apply 2 or more layers allowing each layer to dry before applying the next one.
- Fill first application to just below surface and allow to dry. Apply second coat and blend to match surrounding texture.
- May be painted in approximately 2 hours with latex paint. If an oil-based paint is to be used, allow to dry approximately 24 hours.
- For exterior applications, always topcoat with a high quality exterior-grade paint.
- Do not use outside if rain or freezing temperatures are expected within 24 hours. Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- Do not use as a skim coat.

### **FOR BEST RESULTS**

Consult paint manufacturer's recommendations before decorating. To repair large breaks, cracks and holes in stucco surfaces, use DAP Stucco Patch, dry mix.

## Typical Physical & Chemical Characteristics:

Consistency	Heavy Paste
Vehicle	Polyvinyl Acetate
Volatile	Water
Filler	Inert Filler
Odor	Mild
Weight/Gallon	15.2 lbs/gallon
Volume Solids	69.4%
Application Temperature	Above 40°F
Service Temperature	-20°F to 150°F
Shelf Life	1 year
Freezing	Freeze/thaw stable 5 cycles at 0°F
Drying Time	Approximately 2 hours with latex paint (depending on temperature, humidity and depth of fill)
Paintability	Prime before painting with latex or oil based paint
Coverage	1 qt = 12-18 sq. ft. / 1 gal = 48-72 sq. ft
SDS Number	00079915005

NOTE: These figures are approximate and may vary with job site conditions.



# TECHNICAL DATA SHEET

## Cleanup & Storage Recommendations:

- Wash tools immediately after use with water.
- Dried material must be removed by scraping or sanding.
- Be sure container lid/cap is closed and tightly sealed.
- Store in a cool, dry place away from extreme heat or cold.

## Safety Information:

Contains: Crystalline silica Sanding of this product may generate dust. Inhalation of dust may cause adverse pulmonary and respiratory effects. May cause eye and skin irritation. Do not breathe dust. Use only with adequate ventilation. Ensure fresh air entry. Wet sanding is recommended to reduce dust exposure. When sanding, wear a NIOSH-approved dust mask. Harmful if swallowed. Do not ingest. Avoid contact with eyes, skin and clothing. Wear gloves and safety glasses. Close container after use. Wash thoroughly after handling.

**FIRST AID:** SKIN: Wash thoroughly. EYE: immediately flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention if complications arise from any exposure. **For emergencies**, call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit [phenopatch.com](http://phenopatch.com).

**KEEP OUT OF REACH OF CHILDREN.**

## Warranty Information:

- If product fails to perform as directed, within one year from the date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund.
- DAP will not be responsible for incidental or consequential damages.

## Disclaimer:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use.

## Company Information:

Manufacturer: PHENOMENAL BRANDS, Phenopatch Products, A division of DAP Products Inc.

2400 Boston Street, Baltimore, MD 21224

Usage Information: Call 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on "Ask the Expert"

Order Information: 800-327-3339

Fax Number: 410-558-1068

Also visit the Phenopatch website at [phenopatch.com](http://phenopatch.com).