



TECHNICAL DATA SHEET

1/25/2018



DAP® PHENOPATCH® PATCH-N-PAINT® Lightweight Spackling

Product Description: DAP® PHENOPATCH® PATCH-N-PAINT® **Lightweight Spackling** lets you patch and prime in one easy step, saving time and money. It dries fast with no need to sand or prime, letting you paint in minutes. It is easy to apply with one strike of the putty knife. Won't shrink or crack. Ideal for repairing holes, cracks and dents in drywall, plaster, wood and stucco. **PATCH-N-PAINT** is low in odor and for interior and exterior use.



Featured & Benefits:

- Patch & Prime in One Step
- Fast Drying – 30 minute Paint Ready
- No Sanding
- Won't Shrink/Crack
- Interior/Exterior use

Suggested Uses:

Ideal for filling holes, cracks, crevices, dents and defects on:

- Drywall
- Plaster
- Wood
- Stucco

Available In:

SKU #	Description	Size	Package Type	Case Pack	Color
7079812315	PATCH-N-PAINT Lightweight Spackling	2.8 Fl. Oz. (83 mL)	Tube	12 PK	Off White
7079801602	PATCH-N-PAINT Lightweight Spackling	8 Fl. Oz (237 mL)	Tub	24 PK	Off White
7079816111	PATCH-N-PAINT Lightweight Spackling	32 Fl. Oz. (946 mL)	Tub	8 PK	Off White
7079801517	PATCH-N-PAINT Lightweight Spackling	128 Fl. Oz. (3.78 L)	Tub	4 PK	Off White



TECHNICAL DATA SHEET

Surface Preparation & Application Instructions:

- Surface must be clean, dry and free of foreign material.
- Mix gently before use.
(When using the 2.8 oz tube, remove top, grip tube bottom & twist up a very small amount (about 1/16") of filler. Either apply directly to surface or using built-in spackling knife, scrape off spackling from top of tube & apply to wall)
- Using a clean putty knife, press spackling into hole or crack.
- Draw blade firmly across the surface to remove excess material in one strike.
- For a smoother finish, dip putty knife into water and lightly smooth spackling.
- One application is usually sufficient for small repairs.
For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
- May be painted within minutes with a latex paint. Please follow paint manufacturer's instructions for application.
- If sanding is desired, or if an oil-based paint is to be used, allow to dry thoroughly (approximately 24 hours).
- Clean tools immediately with water.

For Best Results:

- Do not apply when temperatures are below 40°F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior applications, first apply exterior-grade primer, then apply spackling and finish with coating of quality exterior-grade paint.
- Do not use for tuck pointing applications on brick.

Typical Physical & Chemical Characteristics:

Consistency	Thick Paste
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler
Odor	Mild
Specific Gravity	0.43
Volume Solids	75% by volume
Application Temperature	40°F or higher
Service Temperature	-20°F to 150°F
Shelf Life	12 months
Freezing	Freeze/thaw stable 5 cycles at 0°F
Painting	Takes either oil or latex-based paint
SDS Number	00079942005



TECHNICAL DATA SHEET

Cleanup & Storage Recommendations:

- Wash tools immediately after use with water.
- Dried material must be removed by scraping or sanding.
- Be sure container lid/cap is closed and tightly sealed.
- Store in a cool, dry place away from extreme heat or cold.

Safety Information:

Contains: Sodium silicate glass, calcium carbonate & sodium borate. May be harmful if inhaled. May cause eye, skin & respiratory irritation. Do not ingest. Harmful if swallowed. Don't breathe vapors or dust. Use only w/adequate ventilation. Ensure fresh air entry. Prevent build-up of dust and vapor by opening windows and doors. Dry sanding of this product may generate dust. Inhalation of dust may cause lung damage. When sanding, wear a NIOSH-approved dust mask. Avoid contact w/eyes, skin & clothing. Wear gloves & safety glasses. Wash thoroughly after handling.

FIRST AID: SKIN: Wash thoroughly. EYE: Immediately flood w/large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention if complications arise from any exposure. For emergencies, call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS contact your supplier or visit phenopatch.com.

KEEP OUT OF REACH OF CHILDREN

Warranty Information:

- If product fails to perform as directed, within one year from the date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund.
- DAP will not be responsible for incidental or consequential damages.

Disclaimer:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use.

Company Information:

Manufacturer: PHENOMENAL BRANDS, Phenopatch Products, A division of DAP Products Inc.
2400 Boston Street, Baltimore, MD 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339

Fax Number: 410-558-1068

Also visit the Phenopatch website at phenopatch.com.