



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® PHENOPATCH® PATCH-N-PAINT® Lightweight Spackling

PRODUCT DESCRIPTION

DAP® PHENOPATCH® PATCH-N-PAINT® **Lightweight Spackling** lets you patch and prime in one easy step, saving time and money. It dries fast with no need to sand or prime, letting you paint in minutes. It is easy to apply with one strike of the putty knife. Won't shrink or crack. Ideal for repairing holes, cracks and dents in drywall, plaster, wood and stucco. **PATCH-N-PAINT** is low in odor and for interior and exterior use.



PACKAGING	COLOR	UPC
2.8 oz. Tube	Off-White	7079812315
Half Pint	Off-White	7079801602
Quart	Off-White	7079801611
Gallon	Off-White	7079801517

KEY FEATURES & BENEFITS

- Patch & Prime in One Step
- Fast Drying – 30-minute Paint Ready
- No Sanding Required
- Won't Shrink/Crack
- Interior/Exterior use

SUGGESTED USES

Ideal for filling holes, cracks, crevices, dents and defects on: Drywall, Wood, Plaster & Stucco.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- Do not apply when temperatures are below 40°F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior applications, first apply exterior-grade primer, then apply spackling and finish with coating of quality exterior-grade paint.
- Do not use for tuck pointing applications on brick.

APPLICATION

1. Surface must be free of grease, oil and other foreign matter. Sweep or blow surface with compressed air to remove all mud, dirt, dust and other loose debris.
2. Mix gently before use.
(When using the 2.8 oz tube, remove top, grip tube bottom & twist up a very small amount (about 1/16") of filler. Either apply directly to surface or using built-in spackling knife, scrape off spackling from top of tube & apply to wall)
3. Using a clean putty knife, press spackling into hole or crack.
4. Draw blade firmly across the surface to remove excess material in one strike.
5. For a smoother finish, dip putty knife into water and lightly smooth spackling.
6. One application is usually sufficient for small repairs.
For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
7. May be painted within minutes with a latex paint. Please follow paint manufacturer's instructions for application.
8. If sanding is desired, or if an oil-based paint is to be used, allow to dry thoroughly (approximately 24 hours).
9. Clean tools immediately with water.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Thick Paste
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Odor	Mild
Gravity	0.43
Solids	75% by volume
Application Temperature	40°F or higher
Service Temperature	-20°F to 150°F
Shelf Life	12 months
Freezing	Freeze/thaw stable 5 cycles at 0°F
Painting	Takes either oil or latex-based paint

CLEAN UP & STORAGE

Wash tools immediately after use with water. Dried material must be scraped, or sanded away. Be sure container lid/cap is closed and tightly sealed. Store in a cool, dry place away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com