



Technical Bulletin

PHENOMENAL BRANDS, Phenopatch Products
A division of DAP Products Inc.
2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-779-3265

Revised: 7/19/07

Phenopatch™ All-Purpose Spackling Paste

- Ready to use formula
- Paintable
- Easy to Sand
- Interior/Exterior use

Packaging: ½ pt (237 ml), 1 quart (.946 L), 1 gallon (3.78 L)
Color: White
UPC Numbers: 0 70798 76858 1, 0 70798 76857 4, 0 70798 76859 8

Company Identification:

Manufacturer: PHENOMENAL BRANDS, Phenopatch Products, A division of DAP Products Inc.,
2400 Boston St., Baltimore, Maryland 21224
Usage Information: 410-779-3265 9:00 am to 7:00 pm EST.
Order Information: 410-779-3265
Also, visit the Phenopatch website at www.phenopatch.com

Product Description:

Phenopatch™ All-Purpose Spackling Paste is a ready to use spackle for repairing and filling cracks and holes in wallboard, drywall, plaster, wood, brick and stone. It spreads easily for fast professional repairs that will not crack, crumble or flake. Phenopatch™ All-Purpose Spackling Paste dries hard, sands easily and can be painted. Easy water clean-up formula.

Suggested Uses:

Ideal for filling and covering:

- Primed wood
- Wallboard/drywall/plaster
- Brick
- Stone
- Nail heads
- Fill splits

Surface Preparation & Application:

Preparation:

- Surface must be clean, dry and firm.
- Do not apply at temperatures below 40°F.
- Lightly sand to ensure adhesion. Bare wood should be primed prior to application with latex primer.

Application:

1. Using a putty knife, thoroughly fill all cracks.
2. Finish flush with surface.
3. Deep fills over 1/4" may require two separate applications.
4. Allow to dry for 1-5 hours depending on temperature, humidity and depth of fill before painting or priming.
Light sanding may be necessary.
5. Priming is recommended prior to painting with a high-gloss paint.
6. May be painted with latex or oil-based paints.
7. For exterior applications, must be protected with a weather-resistant coating.
8. Store away from extreme heat or cold.

Physical & Chemical Characteristics:

Consistency:	Heavy Paste
Vehicle:	Vinyl-Acrylic Polymer
Volatile:	Water
Filler:	Inert Filler
Odor:	Mild
Weight per gallon:	15.0-16.0 lbs
Solids:	72-77 wt%
Application Temperature Range:	Above 40° F
Service Temperature Range:	-20°F - 150°F
Shelf Life:	1 year
Freeze/Thaw Stability:	Yes
Drying Time:	1 -5 hours depending upon temperature, humidity and depth of fill
Paintability:	Paintable with latex or oil-based paints

MSDS No: 000 79944 005

Clean Up & Storage:

Clean tools immediately with warm soapy water. Store away from extreme heat or cold.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by calling 410-779-3265 or visit www.phenopatch.com.

Satisfaction Guaranteed: If not satisfied with product's performance when used as directed, return used container and sales receipt to PHENOMENAL BRANDS, Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. PHENOMENAL BRANDS will not be liable for incidental or consequential damages.